



## KEY FEATURES

- Intel® 9<sup>th</sup>/8<sup>th</sup> Gen LGA1151 Processors, up to 35W
- 2 x 260-pin SO-DIMM up to 32GB DDR4 2133 MHz (16GB per DIMM)
- 4 x USB 3.1 Gen1, 1 x USB 3.1 Gen1(Type C), 4 x USB 2.0, 1 x M.2 Key E, 1 x M.2 Key M, 1 x COM, 1 x SATA
- 1 x Realtek 1 Gigabit LAN
- Supports dual display, 1 x HDMI 2.0, 1 x VGA
- 1 x 19V/90W AC-DC power brick adapter
- 262.35 x 177.35 x 64.7mm, Fanless Barebone

## SPECIFICATIONS

### Processor System

CPU	Intel® 9 <sup>th</sup> /8 <sup>th</sup> Gen LGA1151 Processors, up to 35W
Chipset	H310
Socket	LGA1151
BIOS	AMI SPI 128 Mbit

### Memory

Technology	Dual Channel DDR4 2133 MHz
Capacity	32 GB (16 GB per DIMM)
Socket	2 x 260-pin SO-DIMM

### Graphics

Controller	Intel® HD Graphics
HDMI	HDMI 1.4a Max resolution up to 4096x2160@24Hz
DisplayPort	DisplayPort 1.2a Max resolution up to 4096x2160@60Hz
VGA	Max resolution up to 1920x1200@60Hz
LVDS	N/A
eDP	N/A
DVI	N/A
MultiDisplay	Dual Display

### Expansion Slot

mini-PCIe/ mSATA	N/A
mini-PCIe	N/A
M.2	1 x M.2 (KEY E, 2230) with PCIe x1 and USB 2.0 for Wireless
SIM Socket	N/A

### Audio

Interface	Realtek ALC233, High Definition Audio
-----------	---------------------------------------

### Ethernet

Controller/ Speed	1 x Realtek RTL8111H with 10/100/1000 Mbps
Connector	2 x RJ-45

### Storage

M.2	1 x Key M (2280)with PCIe x4 and SATA3 for SSD
mSATA	N/A
SATA	1 x SATA3 (6.0Gb/s)
eMMC	N/A

### Front I/O

HDMI	N/A
DisplayPort	N/A
USB	2 x USB 3.1 (Gen1), 2 x USB 3.1 (Gen1)(Type C)
Audio	2 (Mic-in, Line-out)

### Rear I/O

HDMI	1 x HDMI 1.4a
DisplayPort	1 x DisplayPort 1.2a
VGA	1
DVI	N/A
Ethernet	1 x Realtek 1 Gigabit LAN
USB	4 x USB 2.0
Audio	N/A
COM	1 x COM (RS-232)
PS2	N/A

### Watchdog Timer

Output	From Super I/O to drag RESETCON#
Interval	256 Segments, 0, 1, 2, ...255sec

### Power Requirements

Input PWR	1 x 19V/90W AC-DC power brick adapter
Power On	AT/ATX Supported - AT : Directly PWR on as power input ready - ATX : Press button to PWR on after power input ready

### Environment

Operating Temp	0°C ~ 50°C
Storage Temp	-40° C ~ 85° C
Operating Humidity	5% ~ 90%
Storage Humidity	5% ~ 90%

### Mechanical

Construction	Aluminum housing
Mounting	N/A
Dimensions (W x H x D)	262.35 x 177.35 x 64.7mm
Weight	Net Weight: 2.8kg

### Others

OS Support	Windows 10
TPM	N/A
Certifications	CE, FCC Class A
Packing List	1 x 19/90W Power Adapter 1 x Screw Package 1 x Product DVD